



SETTING THE STAGE FOR SUCCESS



26 Alco PL Lansdowne, MD 21227



301.850.7006



mail@klassicsound.com



www.klassicsound.com



APEX 2016

Meet the APEX 2016! Strong, and versatile, this mobile stage offers impressive presence in a portable package. The APEX 2016 is suitable for small to medium sized productions, providing a logical and economical solution for a variety of applications.

PRODUCT FEATURES

- 20' x 16' standard stage deck
- Additional decking available for build out
- 700 lbs load limit per fly bay
- 1,000 lbs. load limit per upstage and downstage truss
- Optional banner package
- 30 min. 1 hour installation time





BIG PRODUCTION IN AN AFFORDABLE PACKAGE

BRANDING

With over 500 sq ft of advertising space available, an APEX 2016 banner package will:

- Leverage your brand to it's fullest.
- Provide premium sponsorship opportunities.
- Maximize your revenue stream.

Inquire within to build a custom banner package for your event.







APEX 2016 TECH SPECS

Stage Roof	Trailer	Stage Deck	Other
Covered Roof: 22'9" x 26'	Trailer Length: 25' 6"	Floor Size: 20' x 16'	Install Time: 30min - 1hr
Deck to Bottom of Upstage I-Beam: 11' 5"	Trailer Width: 102"	Floor Height: 45" - 69"	Power Source: 12VDC Pump System
Slide Out Length: 2'3"	Trailer Height: 11' 10"	Ground to Roof: 15' 6"	Personnel Required: 2
Deck-Bottom of Ctr-I-Beam: 11' 8"	Cargo Space: 7' 6" x 4' 8"	Total Floor Load Rating: 150 lb/sqft	Site Prep: None
Surface: Fiberglass / Alum	Cargo Capacity: 4,000 lbs	Structure: Marine Plywood / Alum	Hauling Mode: Pick-Up Truck, Bumper Pull, 2-5/16" Hitch
Total Roof Capacity: 3,400 lbs	Trailer Weight: 8,000 lbs	Floor Support: (5) 8,000 lbs Jacks	
Deck to Roof Top: 12' 10"	Tongue Weight: 800lbs		
Upstage I-Beam: 1,000 lbs even dist	Rear Axle Rating: 6,000 lbs		
Deck to Bottom of Downstage I-Beam 11'11"	Front Axle Rating: 6,000 lbs		
Downstage I-Beam (Front of Stage): 1,000 lbs even dist.	GVWR: 12,000 lbs		
Fly Bays: 700 lbs ea			







A Mail@klassicsound.com

